

U-Series®

Fiber Distribution Hub



FDH-1000-144

Ideal for low density PON applications, this cost effective OSP cabinet provides secure and flexible integration of FTTx deployments.

Each cassette telescopes forward which improves connector access. Providing better fiber management the U-Series saves time and reduces network errors for system operators.



Features

- > U-Series Cassettes
- > Easy connector access
- > 144 FTTx Distribution ports
- > 24 Feeder Express ports
- > Five Ruggedized Splitter Slots
- > 36 Connector Storage Holders
- > Front & Rear Door Access
- > Optional Riser or Pole Mount Kit



FDH-1000-144

FIBER DISTRIBUTION HUB

Specifications

Cabinet Dimensions (Without Riser or Pole Mount Bracket)	21" H x 18.125" W x 16" D
Optional: Riser Dimensions	12" H x 18.125" W x 16" D
Weight	49.5 lbs.
Feeder/Express Ports	12 or 24
Cable Entrances	4 - Bottom only
Mounting Options	Vault mount, pole mount, pad mount
Optional: Stub Cable Types	Indoor/Outdoor, Outdoor Dielectric, Outdoor Armored
Cassette Positions	14 (U-Series Cassettes)
Connector Types	SC/UPC, SC/APC, LC/UPC, LC/APC
Splice Capacity	12 splices in each Cassette
Ruggedized Splitter Slots	5
Material	0.125" aluminum with almond powder coating

Connector Storage Holders

Telescoping Feature of U-Series Cassette

5 Hardened splitter slots



Fiber Management Spools

FIBERONE® builds products that are solid and flexible, supporting a wide range of configurations, densities, and connector options. We engineer them with excellence and manufacture them to perfection, right here in the U.S.A.