

HDST-72 : 72 Fiber High Density Rack Mount Splice & Patch Panel



Description:

The HDST-72 provides a flexible and durable solution for rack mount fiber terminations. Capable of splicing and terminating up to 72 fibers in a 19" or 23" rack. Unit is assembled with compact, duplex LC six-pack adapters to maximize space. With the splice option, available splice trays are easily assembled and accessed from the front of the panel. Each unit accepts up to six plug in adapter panels and three 24-fiber splice trays. Typical applications for the HDST-72 include situations where outside plant or riser cables are spliced or terminated on the back of the connect.

Features:

- 2U High
- Reversible 19" or 23" Rack Mount
- Splice & Terminate up to 72 Fibers
- Duplex LC Connectors
- Easy Front & Rear Access
- Protective Drop Cover

Specifications:

Part Number	#151036-BLK
Dimensions	H: 3.5 in. W: 17 in. D: 12 in.
Construction	16 Gauge CRS Steel w/ Powder Coat Finish & Lexan Front Cover
Mounting Options	Reversible 19" or 23" Rack Mount
Fiber Count	Seventy-Two (72) Fibers
Adapter Positions / Options	Twelve (12) / SC, ST, LC, FC or Blank
Splice Tray Size	8.75 Inches
Splice Tray Positions	Three (3)
Color Options	Beige or Black
Provided Accessories	Rack Mounting Screws, Cable Ties, Cable Management Clips, Labels & Installation Instructions