

## OS2 Patch Cords

### Description:

FIBERONE® OS2 fiber optic patch cords are manufactured to standard or custom lengths, colors, connector types and jacket thickness. Available in either a riser rated or fire-retardant plenum jacket with APC or UPC - SC, LC, FC or ST connectors. These patch cords are ideal for a wide range of applications such as, high bandwidth, long-distance telecommunications. FIBERONE finds it crucial to monitor quality by hand testing each patch cord to meet or exceed fiber optic industry standards.



### Features:

- Simplex or Duplex
- Standard or Custom Lengths
- Connector & PVC Jacket Options
- APC or UPC Polish
- Exceeds Industry Standards
- 100% Hand Tested & Guaranteed

### Specifications:

Connector Types	SC	LC	FC	ST
Insertion Loss (dB)	Max. 0.25 Typ. 0.15	Max. 0.25 Typ.0.15	Max. 0.25 Typ. 0.15	Max. 0.25 Typ. 0.15
Reflectance				
APC Polish	- 65 dB	- 65 dB	- 65 dB	N/A
UPC Polish	- 55 dB	- 55 dB	- 55 dB	- 55 dB
Fiber / Cable Type	Corning® SMF-28e Fiber / Riser or Plenum			
PVC Jacket Thickness	2 or 3 mm Diameter			
Operating Temperature	- 20 to 60 °C			