

Universal Connectivity System



UCS-600

Description

Save space and reduce costs of your high density fiber networks with the U-Series; Universal Connectivity System. The UCS-600 chassis accepts twelve Universal Fiber Cassettes, each capable of splicing and terminating 12 fibers allowing for the interconnect of 144 fibers in the 3.5 U chassis.

The telescoping cassette feature provides simplified access to the fiber cassettes and connectors. The removable U-Guard of the UCS Cassettes simplifies front connector access and fiber management which reduces labor and operating costs. The lightweight and durable aluminum construction has a removable top plate and protective corners which allows simplified access for the UCS Cassettes.

Features

- 3.5 U High
- Reversible 19" or 23" Rack Mount
- Splice & Terminate up to 144 Fibers
- Available in White or Black
- Easy Front & Rear Access
- Telescoping design

Specifications

Part Number	156031 (Black) ; 156032 (White)
Dimensions	H: 6.125 in. W: 17.00 in. D: 15.50 in.
Construction	Aluminum chassis, steel mounting brackets
Weight	7.0 lbs.
Mounting Options	Reversible 19" or 23" Rack Mount
Fiber Count	One hundred forty four (144) Fibers
Universal Cassette Positions	Twelve (12)
Provided Accessories	Rack Mounting Screws, Cable Ties, Velcro Ties, Installation Guide